



imageRUNNER C3326i

# RELIABILITY, SECURITY AND HIGH PRODUCTIVITY FROM A COLOUR A3 MULTIFUNCTION PRINTER

Maximise uptime and simplify maintenance with unrivalled device durability



**PRODUCTIVITY**



**SECURITY**



**CONTROL AND MAINTENANCE**



**USER EXPERIENCE**



**CLOUD CONNECTIVITY**



**SUSTAINABILITY**

**Canon**

---

# imageRUNNER C3326i

## PRODUCTIVITY

- Fast warm-up time starts print production more quickly
- Print a wide variety of media types and sizes, continuously in high-volume
- Personalise the user display configuration to enhance document processing efficiency
- Streamline document post-production with optional finishing options, including eco-staple, staple and punch
- Optional encrypted SSD storage extends data storage and is more resistant to vibration and shock for increased reliability

## USER EXPERIENCE

- Easy to use 7-inch/17.8cm touchscreen provides excellent visibility and usability for intuitive handling
- Optimise print, copy, scan and send document workflows to one-touch operation
- Combine multiple settings into one button for super-fast document processing
- Repeat previous jobs at the touch of a button with Timeline setting history

## SECURITY

- Verify System at start up supporting Platform Firmware Resiliency (NIST SP800-193) and Automatic Recovery, SIEM support and McAfee Embedded Control analyse the device in real-time to detect and prevent external attacks

- Set up device authentication, two-factor authentication and device function restrictions for both device and cloud-based security measures
- Optional Encrypted SSD storage extends data protection and is more resistant to vibration and shock for increased reliability
- Upgrade to uniFLOW Online\* for enhanced secure printing, mobile printing, and guest printing from any device
- Data privacy across your network is ensured with IPSec, port filtering and TLS 1.3 & WPA3 support
- Step-up security further with easy-to-programme Security Navigator or let Canon's experts create best solution for your business environment

## CLOUD CONNECTIVITY

- Save scanned documents to your email or Google Drive/Google Workspace using personalised workflows with uniFLOW Online Express
- File Assist automatically names, sorts and create a folder structure for files
- Print wirelessly from mobile devices, with support for Apple AirPrint and Mopria
- Add extra functionality to mobile printing and scanning with Canon's PRINT Business app

## CONTROL AND MAINTENANCE

- Centrally manage all devices on the network with cloud-based remote management options
- Remote Operators Software Kit provides alternative access to device for remote operation of all system functions
- Compatibility with Canon's uniFLOW software solutions allows for tracking and reporting of print jobs
- e-Maintenance can improve uptime through remote diagnostics, automated meter readings and consumables monitoring

## SUSTAINABILITY

- Edit print settings at device-level to reduce paper and toner wastage
- Converting document to digital files minimises paper usage
- Eco-stapling option allows for further reduction of consumables
- Energy saving features, such as Sleep Mode help to decrease power consumption
- Better typical energy consumption (TEC value) compared to previous series minimises running costs

\*uniFLOW Online is available as a Device Based Cloud Subscription for Document Output and Capture Management. Based on business needs, users can upgrade to uniFLOW Online to unlock a range of advanced benefits, including: Increased security with user authentication methods. Personalised workflows to enhance productivity. Reduced wastage by releasing jobs at the device. An intuitive cloud dashboard to leverage real-time data. Greater control over access and usage to reduce print costs.


## QUICK FACTS

- Print, Copy, Scan and Send
- 7-inch/17.8cm WVGA colour touchscreen
- One-touch operation with Timeline and Shared/Personal buttons
- Print speed of up to 26ppm
- Support for a wide range of media types and sizes
- uniFLOW Online Express\* cloud-based print management solution
- Automatic file naming, sorting and folder structure with Filing Assist\*\*
- Document, device and network security from McAfee Protected Control, TLS1.3, WPA3 and SIEM support
- Easy maintenance with automatic firmware updates
- Finishing options include eco staple, staple and punch

\*requires activation

\*\*available with subscription to uniFLOW Online Cloud based print management solution

## TAILORED SOLUTIONS TO MEET EVERY CHALLENGE




Canon's Digital Transformation Services (DTS), bring together our leading hardware and software into an integrated technology ecosystem, designed to support your transformation journey. This offering combines Managed Print Services and Workspace Collaboration solutions, to help you gain transparency and control over the entire document lifecycle.



# imageRUNNER C3326i

# RELIABILITY, SECURITY AND HIGH PRODUCTIVITY FROM A COLOUR A3 MULTIFUNCTION PRINTER

## MAIN CONFIGURATION OPTIONS



This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the product configurator.

**Canon**

# TECHNICAL SPECIFICATIONS

# imageRUNNER C3326i

## MAIN UNIT

<b>Machine type</b>	A3 Colour Laser Multifunctional
<b>Core functions</b>	Print, Copy, Scan, Send and Optional Fax
<b>Processor</b>	1.6 GHz Dual Core Processor
<b>Control Panel</b>	17.8 cm/7 inch TFT LCD WVGA Colour Touch panel
<b>Memory</b>	Standard: 2.0GB RAM
<b>Storage</b>	Standard: (eMMC) 64GB Optional: (SSD) 256GB
<b>Interface Connection</b>	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE802.11b/g/n) OTHERS Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1
<b>Paper Supply capacity (A4, 80gsm)</b>	Standard: 1,200 Sheets Maximum: 2,300 Sheets (with optional Cassette Feeding Unit-AW1)
<b>Paper output capacity (A4, 80gsm)</b>	Standard: 250 Sheets Maximum: 650 Sheets (with optional Inner Finisher-L1 and Copy Tray-T1)
<b>Finishing capabilities</b>	Collate, Group, Offset, Staple, Hole Punch, Eco Staple, Staple On Demand * Finishing capabilities vary, depending on the options selected

## Supported Media Types

Multi-purpose Tray:  
Thin, Plain, Heavy\*, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope  
\* SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper

Upper Cassette:  
Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope\*  
\* Envelope Feeder Attachment Kit B (standard) is required.

Lower Cassette:  
Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope\*  
\* Envelope Attachment Kit A (standard) is required.

## Supported media sizes

Multi-purpose Tray:  
12"x18", 11"x17", Legal, Letter, Letter-R, Executive, Statement, Statement-R

Custom Size/Free Size: 4" x 5-7/8" to 12" x 18", Envelopes (COM10 No.10, Monarch, ISO-C5, DL), Envelope Custom Size ( 3-7/8" x 3-7/8" to 12-5/8" x 18")

Upper Cassette: Letter, Executive, Statement-R  
Custom Size (4-1/8" x 5-7/8" to 11-3/4" x 8-1/2"), Envelopes (ISO-C5) Lower Cassette: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (4-1/8" x 5-7/8" to 12" x 18"), Envelopes6 (COM10 No.10, Monarch, DL)  
\* Envelope Attachment Kit A (standard) is required.

## Supported media weights

Multi-purpose tray: 52 to 300 gsm  
Upper/Lower Cassette: 52 to 256 gsm  
Duplex: 52 to 220 gsm  
4 Seconds or Less\*

## Warm-Up Time (Quick start mode:ON)

\*Time from device power on to when copy icon appears and is enabled to operate on the touch panel display  
From Sleep Mode: 10 Seconds or Less

10 Seconds or Less\*  
\*Time from device power on, until copy ready (not print reservation)

## Dimensions (W x D x H) Installation Space (W x D) Weight

565 x 687 x 891 mm  
1168 x1116 mm  
Approx. 74.7 kg including toner

## PRINT SPECIFICATIONS

### Print Speed

1-sided (BW/CL):  
Up to 26/26 ppm (Letter), Up to 20/20 ppm (Letter-R),Up to 15/15 ppm (Legal/11"x17")

2-sided (BW/CL):  
Up to 26/26 ipm (Letter), Up to 20/20 ipm (Letter-R), Up to 15/15 ipm (Legal/11"x17")

### Print Resolution (dpi)

Up to 1200 x1200

### Page description languages

Standard: UFR II, PCL6  
Optional: Adobe® PostScript®3™

## Direct Print

Supported file types:  
RUI: PDF, EPS, TIFF/JPEG, XPS  
USB Memory: PDF, TIFF/JPEG, XPS  
Network Place: PDF, TIFF/JPEG, XPS

## Printing from mobile and cloud

AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print by Microsoft  
A range of software solutions is available to provide printing from mobile devices and cloud-based services depending on your requirements. Please contact your sales representative for further information

## OS Standard Printing

Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2 or later), iOS (15.2 or later), iPadOS

## Fonts

PS fonts: 136 Roman  
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT  
J/K/S/T\* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts\*\*  
\* Requires optional PCL INTERNATIONAL FONT SET-A1  
\*\* Requires optional BARCODE PRT KIT-D1

## Print Features

Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/ Orientations, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

## Operating System

UFR II: Windows® 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)  
PCL: Windows®8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022  
PS: Windows®8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, Mac OS X (10.11 or later)  
PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)

## COPY SPECIFICATIONS

### Copy Speed

1-sided (BW/CL):  
Up to 26/26 ppm (Letter), Up to 20/20 ppm (Letter-R),Up to 15/15 ppm (Legal/11"x17")  
2-sided (BW/CL):  
Up to 13/13 ppm (Letter), Up to 10/10 ppm (Letter-R),  
Up to 7/7 ppm (Legal/11"x17")  
(BW/CL): Approx. 7.0 / 8.7 seconds or less

### First-Copy-Out Time

600 x 600

### Copy resolution (dpi)

Up to 999 copies

### Multiple Copies

Automatic or Manual (9 Levels)

### Copy Density

25% - 400% (1% Increments)  
Preset reduction/enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%

### Magnification

### Copy Features

Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Sharpness, Erase Frame, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved copy, Copy Sample

## SCAN SPECIFICATIONS

### Type

Standard: Duplexing Automatic Document Feeder [2-sided to 2-sided]

### Document Feeder Paper Capacity (80 gsm)

Up to 100 sheets

### Acceptable Originals and weights

Platen: Sheet, Book and 3-Dimensional objects  
Document Feeder media weight :

1-sided scanning: 30 to 128 gsm (BW), 64 to 128 gsm (CL)

2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)

### Supported media sizes

Platen: max. scanning size: 297.0 x 431.8 mm

Document Feeder media size:

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" x 5-1/2" to 12" x 17" (69.9 mm x 139.7 mm to 304.8 mm x 431.8 mm)

# TECHNICAL SPECIFICATIONS

# imageRUNNER C3326i

<b>Scan Speed</b>	DADF (ipm: BW/CL, A4): 1-sided Scanning: 70/70 (300 dpi, send), 51/42 (600 dpi, copy) 2-sided Scanning: 35/35 (300 dpi, send), 25.5/25.5 (600 dpi, copy)	<b>SECURITY SPECIFICATIONS</b>	User Authentication (Picture Login, Picture and PIN Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
<b>Scan Resolution (dpi)</b>	Scan for Copy: up to 600 x 600 Scan for Send: (Push,BW) up to 600 x 600, (Pull,BW) up to 600 x 600 (Push,CL) up to 300 x 300, (Pull,CL) up to 300 x 300 Scan for Fax: up to 600 x 600	<b>Authentication and Access Control</b>	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Recieve Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS*), Send Data Security (Restricted E-mail/ File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support) *1 Requires optional uniFLOW Online / uniFLOW *2 Requires optional Universal Send Digital User Signature Kit-C1
<b>Pull Scan Specifications</b>	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows* 8.1/10/11/ Server2012/Server2012 R2/Server 2016/Server 2019/Server2022	<b>Document Security</b>	Standard Storage Initialize, Job Log Conceal Function, Protecting MFP Software Integrity, Checking MFD Software Integrity & Platform Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at Startup, Runtime Intrusion Detection enabled with McAfee Embedded Control), Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Security Policy Setting, Remote Management Two-factor Authentication
<b>Scan Method</b>	PushScan, PullScan, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud-based services (uniFLOW Online/Online Express)	<b>Network Security</b>	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, WPA3 support, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling/Enabling (Network Protocols/Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Scan and Send -Virus Concerns for E-mail Reception
<b>SEND SPECIFICATIONS</b>		<b>Device Security</b>	
<b>Destination</b>	Standard: E-mail/Internet FAX (SMTP), SMB3.1.1, FTP, WebDAV, Optional: Super G3 FAX	<b>Device Management and Auditing</b>	
<b>Address Book</b>	LDAP (2,000)/ Local (1,600) /Speed dial (200)	<b>ENVIRONMENTAL SPECIFICATIONS</b>	
<b>Send resolution (dpi)</b>	Push: 100 x 100, 150 x 150, 200 x 100 (Normal), 200 x 200 (Fine), 200 x 400*(SuperFine), 300 x 300, 400 x400*(UltraFine), 600 x 600* Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *Colour mode is black and white only	<b>Operating Environment</b>	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity) 220-240V 50/60Hz 4A
<b>Communication protocol</b>	File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV Email/iFax: SMTP (send), POP3 (receive)	<b>Power source</b>	Maximum: Approx. 1,500 W Standby: Approx. 44 W*1 Sleep mode: Approx. 2.0W*2, Approx. 1.0W*3
<b>File Format</b>	Standard: TIFF (MMR), JPEG *, PDF (Compact, Searchable, PDF/A-1b, Encrypted), XPS (Compact, Searchable), PDF/XPS (Device Signature, Office Open XML (PowerPoint, Word)) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature) *Single page only	<b>Power consumption</b>	*1 Reference value: measured one unit * Wireless LAN power serve mode OFF * Wireless LAN power serve mode ON *3 Sleep mode is not available in all circumstances due to certain settings. Typical Electricity Consumption (TEC)*: 0.32 kWh Note: As per US Energy Star 3.0
<b>Universal Send Features</b>	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation	<b>Noise levels (BW/CL)</b>	<u>Sound Power Level (LWA,m)</u> Active (1-sided) : 6.0B*1, 0.3B*1  <u>Sound Pressure Level (LpAm)</u> Bystander's position: Active (1-sided) : 46 dB*1  *1 Reference value: measured only one unit with ISO7779, described with ISO9296:2017 Blue Angel (Applied for)
<b>FAX SPECIFICATIONS</b>		<b>Standards</b>	
<b>Maximum Number of Connection Lines</b>	1	<b>CONSUMABLES</b>	
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps	<b>Toner *1</b>	GPR-66 Toner BK/C/M/Y GPR-66L Toner C/M/Y
<b>Compression Method</b>	MH, MR, MMR, JBIG	<b>Toner Yield</b>	GPR-66 Toner BK: 38,000 pages GPR-66 Toner C/M/Y: 25,500 pages GPR-66L Toner C/M/Y: 11,000 pages
<b>Resolution (dpi)</b>	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)		*1 GPR-66L Toner also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 11,000 images
<b>Sending/Receiving Size</b>	*		
<b>FAX memory</b>	* Up to 30,000		
<b>Speed dials</b>	pages Max. 200		
<b>Group dials/destinations</b>	Max. 199 dials Max.		
<b>Sequential broadcast</b>	256 addresses Yes		
<b>Memory backup</b>			
<b>Fax Features</b>	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox		
<b>STORE SPECIFICATIONS</b>			
<b>Memory Media</b>	Standard: USB Memory		



# TECHNICAL SPECIFICATIONS

# imageRUNNER C3326i

## SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting  
Remote management tools

uniFLOW Online Express  
iW Management Console  
eMaintenance  
Content Delivery System

Scanning software

ScanGear

## HARDWARE ACCESSORIES

Card Readers  
Others

IC Card Reader Attachment-B4

## SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1  
PS Printer Kit-CS1

Data Storage

Optional Data Storage Kit-A1

Send Options

Universal Send Trace & Smooth PDF Kit-A1  
Universal Send Digital User Signature Kit-C1

Barcode Printing

Barcode Printing Kit-D1

System Accessories

Copy Control Interface Kit-D1

Fax Accessories

Super G3 FAX Board-BN1  
Remote Fax Kit-A1

## OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1

Staple Cartridges

Staple-P1

## Software & Solutions



## Compatibility

